
Read First

These suggestions represent generally accepted procedures for successful installation of Colbond Building Products. These instructions may be followed, modified, or rejected by the owner, engineer, contractor or their representative since they, not Colbond Inc., are responsible for planning and executing procedures appropriate to a specific application.

Installation Bulletin

Preparation

- Ensure planter is clean and free of rocks, soil clods, or other debris that may interfere with drainage system performance.
 - Ensure planter bottom has adequate slope that allows proper flow to outlet drain system.
 - Check compatibility of adhesive to membrane.
-

Installation

- Starting at the longest direction of the planter and moving in the opposite direction of the fabric flap, cut the Enkadrain to length and place the fabric flap against the planter bottom.
 - Place a bead of construction adhesive 0.125 inches to 0.25 inches (.3cm to .6cm) in a zigzag pattern along the edge of the Enkadrain that will be covered by the fabric overlap. Lay the next strip of Enkadrain. Repeat this until planter bottom is covered.
 - Measure the perimeter of the planter. Cut a strip of Enkadrain to the measured length and place horizontally around the planter wall.
-

Related Documents

Enkadrain Brochure

Data Sheets

- Enkadrain 3611R
- Enkadrain 3615R
- Enkadrain 3811R
- Enkadrain 9120
- Enkadrain 9611 & 9615

Guide Specifications

- Enkadrain Specifications

**For additional technical assistance please contact: Colbond Inc., P.O. Box 1057, Enka, North Carolina 28728; TOLL FREE: 800-365-7391; PHONE: 828-665-5050; FAX: 828-665-5009; EMAIL: enka-engineered@colbond.com or INTERNET: www.colbond-usa.com.*

Colbond Inc.

PO Box 1057
Enka, NC 28728
Telephone 800-365-7391
Fax 828-665-5009

www.colbond-usa.com

To the best of our knowledge, the information contained herein is accurate. However, Colbond Inc. cannot assume any liability whatsoever for the accuracy or completeness thereof. Final determination of the suitability of any information or material for the use contemplated, of its manner of use and whether the suggested use infringes any patents is the sole responsibility of the user. These products may be covered by patents or patents pending.