



Your Performance Partner

# ACOUSTICAL DOOR



Solid (STC 50)



Accent Window (STC 50)



Full Window (STC 51)



6' (183cm) Double Door (STC 49)

### *Closing the door on noise - A breakthrough in sound isolation.*

In today's finest recording, broadcasting and music facilities every detail matters. Sound isolation is critical for excellence in any performance environment. That's why Wenger engineers and acoustical experts created an acoustical door that not only provides superior sound isolation - it offers an easy, adjustable and reliable fit for any application.

A small gap or imperfection in an acoustical door becomes a large problem. The Wenger Acoustical Door is pre-engineered for consistent, high-integrity installation. And the split-frame design, composed of 14-gauge rigid frame steel construction, ensures proper installation and dependable performance. Compared to kit solutions or doors that assemble with multiple components, Wenger's simple design ensures a good fit time after time. Wenger doors are rated STC 50 or STC 54 and are available in an assortment of configurations.

So whether you're building, renovating, adding on or replacing doors that don't work, the Wenger Acoustical Door is your solution to sound isolation.


# ACOUSTICAL DOOR



Continuous cam-lift hinge eliminates pinch points.




Unique shim tool makes it easy to firmly secure the frame to the wall.




Teflon coated sweep seal features a modified profile for smooth door operation.



Isolated crimp construction for consistent performance.



Continuous dual magnetic seals are pre-aligned - no adjustments required.



Different thickness in window panels and steel door construction prevents same-frequency vibration.

## ACOUSTICAL DOOR SPECIFICATIONS:

- Pre-engineered split-frame for a superior fit.
- Rigid 14-gauge steel split-frame for high integrity installations.
- Isolated crimp construction for more consistent performance.
- Continuous cam-lift hinge improves sound isolation and eliminates pinch points.
- Continuous dual magnetic seals are pre-aligned in the door frame.
- Solid 12-gauge and 14-gauge steel door construction.
- STC 51 rating for a 3' (91 cm) door with full window.
- Easy to install sound absorption foam strips.
- Durable design with maintenance interval of 100,000 cycles.
- Superior Teflon®-coated sweep-seal.
- Stainless steel sill plate.
- Standard mortise pocket for easy lever set installation.
- Door leaf and frame of same width are interchangeable.
- 6' (183cm) double door removable mullion.
- Accommodates wall thickness from 4 1/2" (11cm) to 12 1/2" (32cm).
- Available in four widths: 3' (91cm), 3 1/2' (107cm), 4' (122cm) and 6' (183cm).
- Most models available with a one-hour fire rating.
- Patent Pending.

# Wenger®

**WENGER CORPORATION**  
555 Park Drive, PO Box 448  
Owatonna, MN 55060-0448  
Phone 800.4WENGER  
Fax 507.455.4258  
Customer Service 800.887.7145

**CANADA**  
(Dufferin Liberty Centre)  
219 Dufferin  
Toronto, Ontario, Canada M6K 3J1  
Phone 800.268.0148  
Fax 416.754.3996

**EUROPE**  
Tel +31 26 376 0500  
wenger-europe.com

**BEIJING REPRESENTATIVE  
OFFICE OF WENGER**  
Tel 0086-10-84972502  
Fax 0086-10-84972575

**WORLDWIDE**  
Phone 507.455.4100  
Fax 507.444.0685

**WEB SITE**  
wengercorp.com