

Technical Data & Specifications

TITANIUM™ UDL-30	TECHNICAL DATA
TEST & STANDARD	TITANIUM™ UDL-30 TYPICAL VALUE
Class A Fire ASTM E108	Pass
Nail Sealability ASTM D1970	Pass
Permeability ASTM E96-00	.06 perms
Water Transmission ASTM D4869	Pass
Tear Strength ASTM D226	MD 44 lbs. (20 kg) CD 40 lbs. (18 kg)
Tensile Strength ASTM D751-95	MD 143 lbs. (65 kg) CD 110 lbs. (50 kg)
Burst Strength ASTM D751-95	250 psi (1720 kPa)
Elongation ASTM D751-95	MD 18% CD 18%
Weight per Square ASTM D5261	4.0 lbs. (1.82 kgs)
Nominal Thickness ASTM D1777	25 mils (0.63 mm)
Temperature Range N/A	-70°F (-55°C) to 212°F (100°C)

Test data is based on an average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10%.

TITANIUM™ UDL-30	SPECIFICATIONS
LENGTH PER ROLL:	256' / 78 m
WIDTH PER ROLL:	48" / 122 cm
WEIGHT PER ROLL:	42 lbs / 19 kg
ROLL SIZE:	10.24 sq / 95.1 m ²
ROLLS PER PALLET:	30
PALLET WEIGHT:	1310 lbs / 594 kg

This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures