

SAFETY DATA SHEET

Section 1: Product and Company Identification

Product Group:	Gypsum Core Board Products	
Product Use:	Gypsum panels and decorative molding for interior and exterior applications.	
Chemical Family:	Gypsum, Calcium sulphate dihydrate a naturally occurring mineral. Analyses of gypsum samples demonstrate that the concentration of crystalline silica as quartz is less than 0.025% (wt/wt %). This product contains no asbestos.	
Manufacturer:	CertainTeed Gypsum, Inc. 4300 W. Cypress St., Suite 500 Tampa, FL 33607 USA Web Site: www.certainteed.com	CertainTeed Gypsum Canada, Inc. 2424 Lakeshore Road West, Mississauga, Ontario, Canada L5J 1K4 Web Site: www.certainteed.com
Phone Number:	Professional: 800-233-8990 Consumer: 800-782-8777	Professional: 800-233-8990 Consumer: 800-782-8777
Product Names:	<u>US Product Line:</u> ProRoc® Regular ProRoc® 54" Regular ProRoc® Type X ProRoc® 54" Type X ProRoc® Type C ProRoc® Moisture Resistant ProRoc® Moisture Resistant Type X ProRoc® Sheathing Treated Core ProRoc® Sheathing Treated Core Type X ProRoc® Abuse Resistant Type C ProRoc® Abuse Resistant Type X ProRoc® Interior Ceiling ProRoc® Veneer Plaster Base ProRoc® Veneer Plaster Base Type C ProRoc® Veneer Plaster Base Type X ProRoc® 1/4" Flex ProRoc® Shaftliner Type X ProRoc® Exterior Soffit ProRoc® Exterior Soffit Type C ProRoc® Exterior Soffit Type X ProRoc® Evenwall ProRoc® 54" Evenwall ProRoc® Evenwall Type X ProRoc® 54" Evenwall Type X ProRoc® Moisture and Mold Resistant	<u>Canadian Product Line:</u> ProRoc® Regular ProRoc® 54" Regular ProRoc® Type X ProRoc® 54" Type X ProRoc® Type C ProRoc® Moisture Resistant ProRoc® Moisture Resistant Type X ProRoc® Sheathing Treated Core ProRoc® Sheathing Treated Core Type X ProRoc® Abuse Resistant Type C ProRoc® Abuse Resistant Type X ProRoc® Interior Ceiling ProRoc® Veneer Plaster Base ProRoc® Veneer Plaster Base Type X ProRoc® 1/4" Flex ProRoc® Shaftliner Type X ProRoc® Steps Ceiling Décor Cove and Cornice ProRoc® Moisture and Mould Resistant
24-hour Emergency Number:	In case of an emergency call Team-1 Environmental Services Inc. 1-800-32 SPILL; 1-800-327-7455 (24 hrs)	

Section 2: Hazards Identification

NFPA (USA)	WHMIS (Canada)	Transport Symbol
	<p align="center">Not Controlled</p>	<p align="center">Not Regulated for Transportation</p>

Emergency Overview:

CertainTeed Gypsum board and decorative molding products do not present an inhalation, ingestion, or contact health hazard unless subjected to operations such as sawing, sanding or machining which result in the generation of airborne particulate.

Appearance, Colour and Odor: Solid composite article. Gypsum core boards or decorative molding covered with various colored paper finished surfaces.

USA: While this product is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Canada: While this product is not regulated under WHMIS, this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Potential Health Effects:

ACUTE (short term): see Section 8 for exposure controls

Relevant Route(s) of Exposure:

Inhalation, Skin contact, Eye contact

Inhalation: High concentrations of dust from cutting, sawing, sanding or machining, may cause coughing and mild, temporary irritation following a short-term exposure. Long-term inhalation exposure to dusts can have respiratory effects (see Chronic health effects below).

Ingestion: Avoid ingesting this product. Ingestion may cause gastrointestinal problems.

Skin: Prolonged or repeated contact may cause irritation.

Eye: Direct contact with the eyes may cause temporary irritation as a foreign object in the eye.

CHRONIC (long term): see Section 11 for additional toxicological data

Heavy prolonged industrial exposure to high airborne concentrations of dust may cause impaired lung function. Chronic bronchitis and respiratory tract lesions have also been reported with high level inhaled dust exposures.

Medical Conditions Aggravated by Exposure:

Skin contact may aggravate an existing dermatitis.

Interactions With Other Chemicals:

Tobacco smoking in combination with long-term high dust exposures may increase both smoking and dust-related pulmonary health problems.

Potential Environmental Effects:

No adverse effects known.

Section 3: Composition / Information on Ingredients

Hazardous Ingredients:

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Wt.%</u>
Calcium sulfate	10101-41-4	95 - 100
Cellulose (paper fiber)	9004-34-6	1 - 5
Silica fume	69012-64-2	0.5 - 1.2

Note: See Section 8 of this MSDS for exposure limit data for these ingredients.

Section 4: First Aid Measures

- Inhalation:** If high airborne concentrations of gypsum dust are present, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). If symptoms develop, remove source of contamination or move victim to fresh air. Obtain medical advice.
- Eye Contact:** Do not allow victim to rub eyes. Let the eyes water naturally for a few minutes. Have victim look right and left, and then up and down. If particle/dust does not dislodge, flush with lukewarm, gently flowing water for 5 minutes or until particle/dust is removed, while holding the eyelids open. If irritation persists, immediately obtain medical attention. DO NOT attempt to manually remove anything stuck to the eye.
- Skin Contact:** No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.
- Ingestion:** If irritation or discomfort occurs, obtain medical attention immediately.

Section 5: Fire Fighting Measures

- Flammable Properties:** Gypsum core is non-flammable and does not support combustion.
- Suitable extinguishing Media:** Use water or other extinguishing media appropriate for the surrounding fire.
- Unsuitable extinguishing Media:** Not available
- Explosion Data:**
- Sensitivity to Mechanical Impact:** Not sensitive
 - Sensitivity to Static Discharge:** Not sensitive
- Specific Hazards arising from the Chemical:** Calcium sulfate may decompose into corrosive calcium oxide and oxides of sulfur at about 1450°C (2642°F). Combustion of the product is expected to produce carbon dioxide, carbon monoxide, irritating, and potentially toxic, fumes and dense black smoke.
- Protective Equipment and precautions for firefighters:** As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance.
- NFPA**
- Health:** 1
 - Flammability:** 0
 - Instability:** 0

Section 6: Accidental Release Measures

- Personal Precautions:** Wear proper personal protective equipment as indicated in Section 8.
- Environmental Precautions:** Prevent material from contaminating soil and from entering sewers or waterways.
- Methods for Containment:** No special methods required.
- Methods for Clean-up:** Scoop or shovel spilled material into an appropriate waste container for disposal. Collect all spilled material for proper disposal. Dispose in accordance with federal, state and local regulations.
- Other Information:** Not available

Section 7: Handling and Storage

- Handling:** Avoid creating and breathing dust from this product. Avoid contact with eyes, skin and clothing. Minimize dust generation and accumulation. Wear protective glasses and gloves. If exposure limits are exceeded wear appropriate respiratory protection. (See Section 8)
- Storage:** KEEP OUT OF REACH OF CHILDREN. Store product flat. Protect from water and moisture. See Section 13 for disposal considerations.

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines

<u>Ingredient</u>	<u>ACGIH TLV (8-hr. TWA) (mg/m³)</u>	<u>U.S. OSHA PEL (8-hr. TWA) (mg/m³)</u>	<u>Ontario (Canada) TWAEV (mg/m³)</u>
Calcium sulfate	10 (inhalable fraction)	15 (total dust); 5 (respirable fraction)	10
Cellulose (paper fiber)	10	15 (total dust); 5 (respirable fraction)	10
Silica fume	Not established	80 mg/m ³ / %SiO ₂ (total dust)	2 (respirable)
Particles Not Otherwise Specified	10 (inhalable particles); 3 (respirable)	15 (total dust); 5 (respirable fraction)	10 (inhalable particles); 3 (respirable)

*mppcf: Million particles per cubic foot of air.

Exposure Controls

Engineering Controls: General ventilation is adequate for application of product in its original form. During cutting, sanding operations, monitor dust concentrations in air and provide local exhaust ventilation when any exposure guideline is exceeded.

Personal Protection:

Eye/Face Protection: Wear safety glasses or goggles.

Skin Protection: Wear protective gloves when necessary to prevent irritation to the skin.

Section 8: Exposure Controls/Personal Protection, continued

Respiratory Protection: When dust concentrations in air exceed the occupational exposure guidelines, always take the following precautions:

- Wear a NIOSH approved dust mask.
- Maintain adequate ventilation and air circulation.
- Warn others in the area.
- Use a NIOSH approved respirator when dust levels exceed any of the exposure guidelines listed in the table above.

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or Canadian Standards Association (CSA) Standard Z94.4-93 must be followed whenever workplace conditions warrant a respirator's use.

Other Protective Equipment: Not applicable

General Hygiene Measures: Launder contaminated clothing before re-wearing, or discard. Do not eat, drink or smoke in work areas. Wash hands thoroughly after handling this material. Maintain good housekeeping.

Section 9: Physical and Chemical Properties

Physical State:	Solid	Flash Point & method:	Not applicable – Product is not combustible
Appearance, Colour and Odour:	Gypsum core boards or panels covered with various colored surfaces of paper. Odorless.	Autoignition Temperature:	Not applicable
Odour Threshold:	Not applicable	Flammability Limits in Air:	Not applicable
pH:	7 – 9 (in aqueous slurry)	Vapour Pressure:	Not available
Specific Gravity: (water = 1)	2.30-2.37	Vapour Density: (Air = 1)	Not available
Partition coefficient: (n-octanol/water)	Not available	Evaporation Rate: (n-Butyl Acetate = 1)	Not available
Solubility:	0.2% (approximate)	Boiling Point/Range:	Not applicable
Viscosity:	Not available	Melting Point:	Not applicable
Decomposition Temperature:	1450°C (2642°F)		

Section 10: Stability and Reactivity

Chemical Stability:	Stable.
Conditions to Avoid:	Not available
Incompatible Materials:	Gypsum is a stable, unreactive material under normal workplace conditions. Hazardous reactions may occur with some highly reactive materials or at high temperatures.
Hazardous Decomposition Products:	Gypsum may decompose to form Calcium oxide (CaO) and sulfur dioxide (SO ₂) if product is exposed to extreme heat 1450°C (2642°F). Thermal decomposition products may include organic acids, aldehydes, carbon monoxide, carbon dioxide, and dense black smoke.
Possibility of Hazardous Reactions:	None known

Section 11: Toxicological Information

Acute Toxicity Data

	<u>LD₅₀ Oral</u> (mg/kg)	<u>LD₅₀ Dermal</u> (mg/kg)	<u>LC₅₀ Inhalation</u> (4 hrs.)
Calcium sulfate	Not available	Not available	Not available
Cellulose (paper fiber)	>2 000 (rat)	Not available	>5 800 (rat)
Silica fume	Not available	Not available	Not available

Chronic Toxicity Data

Carcinogenicity:

The table below indicates whether each agency has listed any ingredient as a carcinogen.

	<u>ACGIH</u>	<u>IARC</u>	<u>NTP</u>
Calcium sulfate	Not listed	Not listed	Not listed
Cellulose (paper fiber)	Not listed	Not listed	Not listed
Silica fume	Not listed	Group 3	Not listed

ACGIH: (American Conference of Governmental Industrial Hygienists)

IARC: (International Agency for Research on Cancer)

Group 3: The agent is not classifiable as to its carcinogenicity in humans.

NTP: (National Toxicology Program)

Irritation:	Inhaling high concentrations of dust, during installation of product, may cause coughing and mild, temporary irritation. Dust from this product is irritating to the eyes as a foreign object. Prolonged or repeated contact with dust from this product may be irritating to the skin.
Corrosivity:	Not applicable
Sensitization:	Not applicable
Neurological Effects:	Not applicable
Genetic Effects:	Not applicable
Reproductive Effects:	Not applicable
Developmental Effects:	Not applicable
Other Adverse Effects:	Not applicable
Target Organ Effects:	Lungs.

Section 12: Ecological Information

Ecotoxicity:	Not applicable
Persistence/Degradability:	Not available
Bioaccumulation/Accumulation:	Not applicable
Mobility:	Not available

Section 13: Disposal Considerations

Waste Disposal Method:	Do NOT dump into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage.
United States:	Dispose of in accordance with local, state and federal laws and regulations. RCRA Waste Codes: Not applicable
Canada:	Dispose of in accordance with local, provincial and federal laws and regulations.

Section 14: Transport Information:

<u>U.S. Hazardous Materials Regulation (DOT 49CFR):</u>	Not regulated for transportation
<u>Canadian Transportation of Dangerous Goods (TDG):</u>	Not regulated for transportation
<u>ADR/RID:</u>	Not regulated for transportation
<u>IMDG:</u>	Not regulated for transportation
<u>Marine Pollutants:</u>	Not applicable
<u>ICAO/IATA:</u>	Not regulated for transportation

Section 15: Regulatory Information

USA

TSCA Status: All ingredients in the product are listed on the TSCA inventory.

SARA Title III

Sec. 302/304: None

Sec. 311/312: None

Sec. 313: None

CERCLA RQ: None

California Prop 65: This product may contain a substance known to the State of California to cause cancer.

Canada

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all the information required by the *Controlled Products Regulations*.

WHMIS Status: Not controlled
(for workplace exposures)

New Substance Notification Regulations: All substances in this product are listed on Canada's Domestic Substances List (DSL).

National Pollutant Release Inventory: There are no NRPI reportable substances in this product.

Section 16: Other Information

Prepared by: LEHDER Environmental Services Limited
704 Mara Street, Suite 210
Pt. Edward, ON
N7V 1X4
www.lehder.com

Phone: 519-336-4101

Revision date: November 20, 2007

Revision summary: January 25, 2007: Section 1, New Manufacturer name and contact information; new SDS format.
November 20, 2007: Section 1, Addition to US and Canadian Product lines; Reviewed all sections.

Disclaimer: While LEHDER Environmental Services Limited believes that the data set forth herein is accurate, as of the date hereof, LEHDER makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation and verification.

Manufacturer's Disclaimer: Information listed is believed to be accurate but not warranted or guaranteed.