



ACOUSTICAL UNDERLAYMENT

- Suitable for glue down, nail down, and floating laminate, engineered, and hardwood flooring
- Contains **Ultra-Fresh®**, an antimicrobial protection that resists mold and mildew
- Crushpruf™ technology resists indentation and extends the life of the floor
- Provides cushioned comfort under hard laminate flooring
- Eliminates minor subfloor imperfections
- Offers the industry's best limited lifetime warranty
- Suitable for radiant heat flooring systems

100 sq. ft. (3 ft. x 33.34 ft.)

Acoustical Underlayment For Laminate and All Wood Floors



100% Recyclable



THE ECO-SILENCER HD

Made with recycled granulated rubber tires added to our industry leader, Silencer™ underlayment.

PROTECT OUR ENVIRONMENT! Stop old tires from going to the landfills – use **Eco-Silencer HD**.

GO GREEN! and also generate the building standard LEED credits.

www.foamproducts.com



The **Silencer™**



Foam Products Corporation

Comfort - Performance - Luxury

350 Beamer Road SW Calhoun, GA 30701

706-629-1256 · 800-526-3626

Fax: 706-625-0855

www.foamproducts.com

The Eco Silencer HD™

*Recycled granulated tires/polyurethane foam
Acoustical Underlayment*

PROPERTY

FPC Item No.

MATERIALS

ACOUSTICAL

THICKNESS

MOLD, MILDEW, BACTERIAL RESISTANT

THERMAL RESISTANCE (R VALUE)
(ASTM C518)

COMPRESSION SET (ASTM D3574)

FIRE RATING

SMOKE DENSITY (ASTM E-622-95)

BENEFITS

ROLL SIZE

SPECIFICATION

ECOSILDH100 (100sf roll) , ECOSILHD450 (450sf roll)

Recycled granulated tires/high density polyurethane

Testing in progress, >70IIC db , 73STC db

.085" (2.2 mm) , 20 lb Density

Ultra-Fresh® Antimicrobial treatment

.230 (exceptional for radiant heat floor systems)

< 5 % of original thickness

DOC-FF-1-70, Passes

110 Max, Passes

Crushpruf™ technology for superior performance

Excellent sound absorption with ratings of >70 IIC db

Smooths out minor subfloor irregularities up to 1/32"

Non-allergenic and odorless

Suitable for glue-down, nail-down, and floating installations

100% Recyclable, environmentally friendly

3' x 33.34' (100 sq. ft.) , 50 per pallet , 48 pallets per
truck (2,400 rolls = 240,000 sq. ft.)

6' x 75' (450 sq. ft.) , 16 per pallet

Eco-Silencer HD™

*LEED Credits**

MR 4.1 *10% recycled content*

MR 4.2 *20% recycled content*

MR 5.1 *Manufactured within 500 miles of project*

MR 6 *Rapidly renewable resource content*

EQ 4.1 *Low VOC adhesive used on installation*

* The Leadership in Energy and Environmental Design (LEED®) Green Building rating System represents the U.S. Green Building Council's effort to provide a national standard for what constitutes a " Green Building". It is used as a design guideline and certification for architects, designers, and builders seeking to develop high performance, sustainable buildings. The LEED v2.2 rating system for New Construction and Major Renovations is designed to guide and distinguish high-performance commercial and institutional projects, including office buildings, high-rise residential buildings, government buildings, recreational facilities, manufacturing plants and laboratories. The use of Eco-Silencer HD can obtain up to 4 points toward LEED certification.



100% Recyclable

