

Johns Manville Commercial/Industrial Roofing Systems

Built-up Roofing

Product	Use	Description	Size	Standard
GB #605	Base	A heavy weight, high strength, base felt with a coarse mineral surface for cold process built-up roofing systems (Region 3 only)	1 sq. (9.29 m ²) roll	ASTM D 3909
GB #607	Base	A heavy weight, high strength, pliable base or ply felt for cold process built-up roofing systems (Region 3 only)	2 sq. (18.6 m ²) roll	ASTM D 4601
GlasBase™ Plus	Base	Premium, rubber-modified, asphalt-coated, fiber glass base sheet for use in BUR and MB systems	3 sq. (27.9 m ²) roll	ASTM D 4601, Type II
GlasKap®	Cap	Mineral-surfaced, asphalt-coated, fiber glass cap sheet for use in BUR systems	1 sq. (9.3 m ²) roll	ASTM D 3909
GlasKap® Plus	Cap	Mineral surfaced, asphalt coated, fiber glass reinforced cap sheet for use in BUR systems (Region 3 only)	1 sq. (9.3 m ²) roll	ASTM D 5147
GlasPly® IV	Ply	Asphalt-coated, fiber glass ply sheet for use in BUR and MB systems	5 sq. (46.5 m ²) roll	ASTM D 2178, Type IV
GlasPly® Premier	Ply	Premium, asphalt-coated, web process fiber glass ply sheet for use in BUR and MB systems	5 sq. (46.5 m ²) roll	ASTM D 2178, Type VI
GlasTite® Flexible	Flashing	Durable polyester/glass scrim reinforced, asphalt-coated flashing sheet for use in BUR systems	1/2 - 1 1/2 sq. (4.6 - 13.9 m ²) roll	None
PermaPly® 28	Base	Asphalt-coated fiber glass base sheet for use in BUR and MB systems	3 sq. (27.9 m ²) roll	ASTM D 4601, Type II
Ventsulation® Felt	Base	A premium, asphalt-coated, granular, embossed, venting base sheet for use over wet fill decks or in recover applications with BUR and MB systems	1 sq. (9.3 m ²) roll	ASTM D 4897, Type II

Visit www.jm.com for Product Submittal Sheets