

**Johns Manville****Products****SBS Modified Bitumen Products**

<b>Product</b>	<b>Use</b>	<b>Description</b>	<b>Size</b>	<b>Standard</b>
DynaBase	Base	A fiber glass reinforced, SBS modified bitumen base sheet	11/2 sq. (15 m <sup>2</sup> )	ASTM D 6163 Type I, Grade S
DynaClad	Flashing	A foil faced, fiber glass reinforced, SBS modified bitumen flashing or cap sheet, available with copper facing	3/4 sq. (7.0 m <sup>2</sup> )	ASTM D 6298
DynaFlex	Flashing	A flexible polyester/glass scrim reinforced, granular surfaced, SBS modified bitumen flashing sheet	3/4 sq. (7.0 m <sup>2</sup> )	ASTM D 6221 Type I
DynaGlas	Cap	A premium, fiber glass mat reinforced, granular surfaced, SBS modified bitumen cap sheet	1 sq. (10 m <sup>2</sup> )	ASTM D 6163 Type I, Grade G
DynaGlas FR	Cap	A premium, fiber glass mat reinforced, granular surfaced, SBS modified bitumen cap sheet for use in fire-rated systems	1 sq. (10 m <sup>2</sup> )	ASTM D 6163 Type I, Grade G
DynaGlas 30 FR	Cap	A fiber glass mat reinforced, granular surfaced, SBS modified bitumen cap sheet for use in fire-rated systems	1 sq. (10 m <sup>2</sup> )	ASTM D 6163 Type I, Grade G
DynaKap	Cap	A premium fiber glass/polyester composite reinforced, granular surfaced, SBS modified bitumen cap sheet	1 sq. (10 m <sup>2</sup> )	ASTM D 6162 Type II, Grade G
DynaKap FR	Cap	A fire-resistant, premium, fiber glass/polyester composite reinforced, granular surfaced, SBS modified bitumen cap sheet	1 sq. (10 m <sup>2</sup> )	ASTM D 6162 Type II, Grade G
DynaLastic 180	Cap	A 180 gram polyester mat reinforced, granular surfaced, SBS modified bitumen cap sheet	1 sq. (10 m <sup>2</sup> )	ASTM D 6164 Type I, Grade G
DynaLastic 180 FR	Cap	A 180 gram polyester mat reinforced, granular surfaced, SBS modified bitumen cap sheet for use in fire-rated systems	1 sq. (10 m <sup>2</sup> )	ASTM D 6164 Type I, Grade G
DynaLastic 180 S	Cap	A 180 gram, polyester reinforced, smooth surfaced, SBS modified bitumen cap sheet	1 sq. (10 m <sup>2</sup> )	ASTM D 6164 Type I, Grade S
DynaLastic 250	Cap	A 250 gram, polyester reinforced, granular surfaced SBS modified bitumen cap sheet	1 sq. (10 m <sup>2</sup> )	ASTM D 6164 Type II, Grade G
DynaLastic 250 FR	Cap	A 250 gram, polyester reinforced, granular surfaced SBS modified bitumen, fire resistant cap sheet	1 sq. (10 m <sup>2</sup> )	ASTM D 6164 Type II, Grade G
DynaPly	Cap	A premium, smooth-surfaced, fiber glass/polyester mat reinforced SBS cap sheet for use in gravel surfaced MBR systems	1 sq. (10 m <sup>2</sup> )	ASTM D 6162 Type II, Grade S
DynaTred and DynaTred Plus	Roof Walkway	Preformed, skid resistant boards consisting of modified asphalt, reinforcements and fillers with ceramic granule surfaces	32" x 32" (813 mm x 813 mm)	None

\*Material tested in accordance with ASTM D 5147, "Standard Test Methods for Sampling and Testing Modified Bituminous Sheetting Material".

**SBS Modified Bitumen Heat Weldable Products**

DynaWeld Base	Base, Interply	A fiber glass mat reinforced, smooth surfaced, modified bitumen base or ply sheet for heat weldable applications only	1 sq. (10 m <sup>2</sup> )	ASTM D 6163 Type I, Grade S
DynaWeld Cap FR	Cap	A fire resistant, fiber glass mat reinforced, granular surfaced cap sheet for heat weldable applications only	1 sq. (10 m <sup>2</sup> )	ASTM D 6163 Type I, Grade G