

Johns Manville**UltraGard® EPDM Selector Guide****EPDM (ethylene propylene diene monomer)****Standard EPDM Membranes****Advantages: Superior weathering characteristics, excellent elasticity.**

Product	Description	Use	Approx. Thickness	ASTM	Sizes	SPEC
EPDM 45	Cured EPDM	For use in ballasted systems. Contact JM for mechanically attached & adhered specifications. For use as flashing in some applications.	0.045" (1.1 mm)	D 4637 ANSI/RMA IPR-1	Nominal std. sheet sizes; 7' x 50' up to 50' x 150'	SE4B
EPDM 60 FR	Fire-resistant - cured EPDM	For use in ballasted mechanically attached and fully adhered systems. May also be used as a flashing as outlined in JM flashing specifications.	0.060" (1.5 mm)	D 4637 ANSI/RMA IPR-1	Nominal std. sheet sizes; 7' x 50' and up to 40' x 100'	SE6M and SE6A
EPDM 60W	White, cured EPDM	For use in mechanically attached and fully adhered systems. May also be used as a flashing as outlined in JM flashing specifications.	0.060" (1.5 mm)	D 4637 ANSI/RMA IPR-1	Nominal std. sheet sizes 10' x 50' and 10' x 100'	SE6M and SE6A

EPDM XT Clean Roofing Membranes**Advantages: Eliminates the need to clean lap areas and field seams, time and labor saver****Reinforced EPDM Membranes****Advantages: EPDM composition - Polyester scrim reinforcement - Superior weathering - Reinforced construction resists membrane flutter**

Product	Description	Use	Approx. Thickness	ASTM	Sizes	SPEC
EPDM 45R XT	Polyester reinforced, cured EPDM	For use as a single ply membrane in mechanically attached, ballasted and fully adhered systems.	0.045" (1.1 mm)	D 4637 ANSI/RMA-IPR-1	Nominal std. sheet sizes; 4 1/2' x 100' up to 10' x 100'	SE4RM, SE4RA and SE4RB
EPDM 60R XT	Polyester reinforced, cured EPDM	For use as a single ply membrane in mechanically attached, ballasted and fully adhered roofing systems.	0.060" (1.5 mm)	D 4637 ANSI/RMA-IPR-1	Nominal std. sheet sizes; 4 1/2' x 100' up to 10' x 100'	SE6RM, SE6RA and SE6RB

EPDM XT Clean Roofing Membranes**Advantages: Eliminates the need to clean lap areas and field seams, time and labor saver**

Product	Description	Use	Approx. Thickness	ASTM	Sizes	SPEC
EPDM 60FR XT	Fire-resistant - cured EPDM	For use in mechanically attached and fully adhered systems. May also be used as a flashing as outlined in JM flashing specifications.	0.060" (1.5 mm)	D 4637 ANSI/RMA-IPR-1	Nominal std. sheet sizes 10' x 50' up to 10' x 150'	SE6M and SE6A