adhesives



I COLORED CAULKS I

Roppe colored caulks let you finish your flooring installation to perfection with colors that match just right. There's no color we can't create in caulk for you. Perfect for touch-ups and to hide gaps or imperfections that can occur during installation of rubber stair treads and tile, our colored caulks give you an unmatched clean, professionallooking project, no matter what the application.

Choosing the right adhesives can make the difference in the appearance, performance and longevity of your floor.

So, always make Roppe your choice to ensure long-lasting and dependable service. No matter what the application, we have an adhesive right for the job, each specially formulated to be used with Roppe flooring products. In fact, our adhesives must be used for Roppe warranties to apply.



This adhesive meets CRI Green Label Plus criteria.

> Always refer to individual flooring products' 10-Part Specification Sheet for correct trowel size, approved substrates, installation type (i.e., rolling loads & lateral sheer stress) & other specific instructions prior to installation.













ROP435 Solvent-Free Epoxy Flooring (Two-Part) Adhesive







ROPECC Epoxy Caulking Compou



ROP535U Universal (Two-Component) Urethane Enhanced Epoxy Adhesive.



ROP604 ESD (Single-Part) Adhesive



ROP605 ESD (Two-Part) Epoxy Adhesive



(Single-Part) Polyurethane Adhesive



all products

adhesives

Tread Epoxy Caulking-Cartridge CECCXP000-420 (13.5 oz. / 25 L/F)

#205 Cove Base Adhesive 62 L/F per Cartridge 275 L/F Base per Gallon

#210 Cove Base Adhesive 62 L/F per Cartridge 275 L/F Base per Gallon

#319 Stair Tread Adhesive (non-flammable) 90 to 120 S/F per Gallon For Two Surfaces 110 to 135 S/F per Gallon – Single surface application

#375 Rubber & Vinyl Tile Adhesive 125 to 245 S/F per Gallon

#435 Flooring Epoxy Adhesive (non-flammable) 125 to 245 S/F per Gallon

#445 Rop-Cord Adhesive 70-75 S/F per Gallon

#535U Universal (Two-Component) Urethane Enhanced Epoxy Adhesive. 75 to 175 S/F per Gallon

#R604 Single Part ESD Adhesive 125-185 S/F per Gallon

#R605 Two-component ESD Adhesive 125-150 S/F per Gallon

#635 Solvent Free Moisture Cured Polyurethane Adhesive 75-100 S/F per Gallon

Acrylic Latex Caulk Available in colors to match all products 12LF 1/4" bead

All coverages are approximate which can vary due to type of product, substrate, type of installation and recommended trowel size. For more information go to roppe.com.



from date of installation to be free of defects in material and workmanship on all first quality products. Limited Wear Warranty also applies to specific products for non-transit use, based by product design and installation purpose, if installed, maintained and used strictly in accordance with Roppe's written instructions and installed with the recommended Roppe Adhesive. Refer to Roppe Product 10-Part Specification Sheet before proceeding with installation. For any applications not listed, do not proceed with installation regardless of the circumstance. It is the Flooring Installer's direct responsibility to inspect and loose lay the flooring in the room or area prior to installation to determine the proper layout and best overall appearance. Flooring Installer must inspect all material for manufacturing imperfections and irregularities prior to installation. All manufacturing imperfections or irregularities must be reported to the appropriate authority. Any defective material will be replaced at no charge, if the defect is found prior to installation. Roppe will not be liable for labor costs for material that is installed with manufacturing imperfections and irregularities. Roppe reserves the right to inspect the manner and quality of installation of its product claimed defective. In

Roppe products are warranted for a period of one (1) year

no event shall Roppe be liable for incidental or consequential damages, even if some other provision of this Limited Warranty is unenforceable. Roppe will not be liable for labor costs or lost profits resulting from the use of or inability to use the product.

Roppe shall have no liability whatsoever to Buyer in the event the goods become defective if such defect is caused in whole or part by cuts, tears, vandalism, fire, willful destruction, damage from high heels, spiked footwear, improper installation, improper maintenance, subfloor and/or substrate irregularities, accidents, natural causes, or acts of God. Products designated as "seconds", "mill run", "non-conforming", not being of first quality, are sold as-is and Roppe makes no warranties whatsoever, expressed or implied, with respect thereto, including warranties of merchantability or fitness for a particular use. These warranties are expressly in lieu of any other warranties expressed or implied. Roppe products not designed for use in or near commercial kitchens. Roppe products are not designed for outdoor installations, unless specifically noted.

Contact Roppe for limitations, exclusions and additional warranty details. Or for 10-Part Specification Sheets and warranty information, visit our Web site at roppe.com.



Roppe Corporation, U.S.A. 1602 North Union Street Fostoria, Ohio 44830-1158 1.800.537.9527 419.435.8546 Fax: 419.435.1056

roppe.com E-mail: sales@roppe.com

© 2009 Roppe Corporation. Printed in the U.S.A.

Roppe is proud to be a member of the following organizations, committed to the advancement of excellence in their fields:



oppe is a member of the U.S. Green Building Council, hich promotes buildings that are environmentally esponsible. Visit usgbc.com for details.





Craftsman trained to stress attention to detail, respect for project specifications and superior workmanship.











