

| GRATING & CATWALK PRODUCT DETAILS | | | | | | | | | | | |
|--|-------|--------------|-------|---------------|-------|-------------|-------|-------------------|-----------------|------|---|
| | | | | | | | | | | | <i>measurements are approximate and subject to mill tolerance</i> |
| Style | #/SF | Design Sizes | | Opening Sizes | | Strand Size | | Overall Thickness | Meshes Per Foot | | % Open Area |
| | | SWD | LWD | SWO | LWO | Thickness | Width | | SWD | LWD | |
| Carbon Steel | | | | | | | | | | | |
| 2.00# | 2.00# | 1.25" | 5.33" | 1.000" | 3.60" | .135" | .230" | .460" | 10 | 2.25 | 77% |
| 3.00# | 3.00# | 1.33" | 5.33" | .940" | 3.44" | .183" | .264" | .540" | 9 | 2.25 | 60% |
| 3.14# | 3.14# | 2.00" | 6.00" | 1.625" | 4.88" | .250" | .312" | .656" | 6 | 2 | 69% |
| 4.00# | 4.00# | 1.33" | 5.33" | .940" | 3.44" | .215" | .300" | .618" | 9 | 2.25 | 55% |
| 4.27# | 4.27# | 1.41" | 4.00" | 1.000" | 2.88" | .250" | .300" | .625" | 8.5 | 3 | 58% |
| 5.00# | 5.00# | 1.33" | 5.33" | .813" | 3.38" | .250" | .331" | .655" | 9 | 2.25 | 50% |
| 6.25# | 6.25# | 1.41" | 5.33" | .813" | 3.38" | .312" | .350" | .715" | 8.5 | 2.25 | 50% |
| 7.00# | 7.00# | 1.41" | 5.33" | .813" | 3.38" | .312" | .391" | .740" | 8.5 | 2.25 | 45% |
| Aluminum | | | | | | | | | | | |
| 2.00# | 2.00# | 1.33" | 5.33" | .940" | 3.44" | .250" | .387" | .730" | 9 | 2.25 | 48% |
| Stainless Steel Type 304 | | | | | | | | | | | |
| 4.50# | 4.50# | 1.41" | 4.00" | 1.000" | 2.88" | .250" | .300" | .625" | 8.5 | 3 | 58% |

All chart specifications may vary. Please inquire if they are critical to your application.