BULLET RESISTANT

HARDWAR

10

ISO 9001:2000 Certified C.R. LAURENCE COMPANY crlaurence.com I Worldwide Supplier

308 HORNADY TAP AMMO 10 YARDS

BTHP FEDERAL

CUSTOM TRANSACTION WINDOWS MANUFACTURED BY C.R. LAURENCE





Installation by Tower Glass Co. Inc., Woburn, MA.




Installation by Universal Glass and Metal Inc., Detroit, MI.

COMING ATTRACTIONS: The New Yankee Stadium and Mets Citi Field



Installation by Model Glass, Anaheim, CA.





Installation by Architectural Glass & Aluminum, Oakland, CA.

CRL C.R. LAURENCE COMPANY 2

crlaurence.com

PROJECTS BY CRL

MAJOR CORPORATIONS AND OTHER VENUES

- AAMCO
- American Honda Motor Co.
- Amoco
- Best Western
- Brusters
- Burger King
- Charles Schwab
- Chevron
- Circle K
- Coca-Cola

SPORTS VENUES

- Adelphia Coliseum, TN
- American Airlines Arena, FL
- Angel Stadium, CA
- Arrowhead Stadium, MO
- AT&T Park, CA
- Beaver Stadium, PA
- Broward County Arena, FL
- · Busch Stadium, MO
- Comerica Park, MI
- Crew Stadium, OH
- Devils Arena, NJ
- Dodger Stadium, CA
- Dunkin Donuts Center, RI
- Fifth Third Field, OH
- Ford Field, MI
- Fresno AAA Ballpark, CA

- Comcast Cablevision
- Dairy Queen • DHL Worldwide
- Disney Red Cat Theatre
- Disnevland
- El Pollo Loco
- General Motors
- Hollywood Bowl
- Jack in the Box
- Kmart
- Giant Center, PA
- Gillette Stadium, MA
- Grizzlies Ballpark, CA Heinz Field, PA
- Lexington Ballpark, KY Mets Citi Field, NY
- Minute Maid Park, TX
- Nationwide Arena, OH
- New Veterans Memorial Stadium, IA
- Orlando Arena, FL
- · Panthers Stadium, FL
- Penn State University, PA Petco Park, CA
- PNC Park, PA Pocono Raceway, CA
- Qwest Field, WA

• Wal-Mart · Wendy's

• Raley's Ballpark, CA

· Reliant Stadium, TX

· Reser Stadium, OR

Riverfront Stadium, NJ

Rosenblatt Stadium, NE

Sovereign Bank Arena, NJ

RCA Dome, IN

- Knott's Berry Farm Kodak Theatre
- Laredo Entertainment Center
- Lexus Corp.
- McDonald's
- Oklahoma City Court House
- Sysco
- Taco Bell

See our new, full color catalog, with over 170 pages of Transaction Hardware items including

specifications.

May be viewed

online at crlaurence.com

Over 150 full color pages of our Sneeze Guards. Partition Posts, Standoffs. Glass Barrier Systems and more. May be viewed online at crlaurence.com

- Russ Chandler Stadium, GA
- Staples Center, CA • The Crown, OH

• Ryder Center, FL

- Verizon Arena, NH
- Washington Ballpark, PA
- · Yankee Stadium, NY



BULLET RESISTANT PROTECTION LEVEL RATINGS

IMPORTANT NOTE!	PROTECTION Level rating	UL 752 BALLISTICS Description	EXCHANGE WINDOW COMPONENTS Glazing materials speak-thrus counter / shelf frame			
Regarding UL 752 Protection Levels Assessment Protection Levels assigned to various products listed as "Bullet Resistant" are based on testing recognized under the standards established by Underwriters' Laboratories (UL) for bullet resisting	LEVEL M.P.S.A.	Medium Power Small Arms (9mm)	1-5/16" Bullet Resistant Glass; 1-1/4" Bullet Resistant Acrylic; 3/4" Bullet Resistant Lexgard.	CAD101, TTU1 with Bullet Resistant Disc. TTU3 Matches Glazing Protection Level.	All	All
components. Protection Levels listed for options available for Exchange Windows pertain only to the option itself. A Level 1 option used with a Level 3 option will yield an overall Protection Level for the lowest rated option or component.	LEVEL 2 H.P.S.A.	High Power Small Arms (.357 Magnum)	1-5/8" Bullet Resistant Glass. 1" Bullet Resistant Lexgard.	N555, N777, TTU3 Matches Glazing Protection Level.	Special Order	Special Order
PROTECTION LEVEL	LEVEL 3 S.P.S.A.	Super Power Small Arms (.44 Magnum)	1-7/8" Bullet Resistant Glass; 1-1/4" Bullet Resistant Lexgard.	N555C3, N777C3, N666, CLD103, TTU1 with Bullet Resistant Disc. TTU3 Matches Glazing Protection Level.	Special Order	Special Order
3	NOT RATED AS BULLET RESISTANT		1/4" Glass.	405, 410, 425, 430, 543, 549, 834, TTU1, TTU3, SST5, SST7		

BuvLine 6331

11 18 00/CRL








FRAME UNITS



ALUMINUM 4" INSET FRAME


Extruded 6063 T5 aluminum alloy, for walls with a 4" minimum thickness. Unit easily slides into wall opening and is secured by screws through the perimeter frame. Mullion shown is used in windows with multiple lites. Choose window options from specification chart.



ALUMINUM 4-7/8" INSET FRAME


1-7/16" + 1

Extruded 6063 T5 aluminum alloy, for walls with a 4-7/8" minimum thickness. Unit easily slides into wall opening and is secured by screws through perimeter frame. Mullion shown is used in windows with multiple lites. Choose window options from specification chart.




ALUMINUM CLAMP-ON FRAME


Extruded 6063 T5 aluminum alloy, for walls from 5" to 8-1/2" thick. Frame clamps onto wall opening with screws positioned through the inside frame into the threaded section of the outside frame. Mullion shown is used in windows with multiple lites. Choose window options from specification chart.




STAINLESS STEEL 4-7/8" INSET FRAME


Type 304 stainless steel 11 gauge # 4 finish, for walls with a minimum thickness of 4-7/8". Corners are mitered and welded. Mullion shown is used in windows with multiple lites. Choose window options from specification chart.














SPECIFICATIONS

Use This Component Menu to Design the Exchange Window of Your Choice Window Type:

- Exterior Installation with Speak-Thru
- □ Interior Installation with Surround Sound
- Solid Vision Window
- Multi-Lite Window

Glazing Material:

- Any Non-Bullet Resistant Glass
- 3/4" Level 1 Bullet Resistant Lexgard
- □ 1-1/4" Level 1 Bullet Resistant Acrylic
- □ 1-1/4" Level 1 Bullet Resistant Acrylic with SAR Coating
- □ 1-5/16" Level 1 Bullet Resistant Glass
- □ 1" Level 2 Bullet Resistant Lexgard
- □ 1-5/8" Level 2 Bullet Resistant Glass
- □ 1-1/4" Level 3 Bullet Resistant Lexgard
- □ 1-7/8" Level 3 Bullet Resistant Glass
- Glass-Clad Polycarbonates

Speak-Thru Options:

- Standard Non-Bullet Resistant
- Bullet Resistant
- Electronic Non-Bullet Resistant
- Electronic Bullet Resistant
- Surround Sound

Aluminum Frames:

- □ Narrow Inset Type for Walls 4" or Thicker
- Standard Inset Type for Walls 4-7/8" or Thicker
- □ Clamp-On Type for Walls 5" to 8-1/2" Thick

Stainless Steel Frame:

□ Standard Inset Type for Walls 4-7/8" or Thicker (Brushed #4 Finish)

Aluminum Frame Finishes:

- Satin Anodized
- Duranodic Bronze
- Powder Coat (choice of 184 RAL colors)
- Kynar Paint (specify color)

Other Options:

- □ 12" Shelf □ 18" Shelf □ Custom Shelf
- □ No Shelf (for Vision Window)
- Stainless Steel Shelf with Deal Tray
- Laminated Shelf with Deal Tray
- Drain Holes
 Weather Flap
- Sliding Panels
- Custom Options on Request



CRL's Quick Fab orders are given top priority. We will suspend fabrication of stock size units in order to begin work on your windows immediately, and give your order our full attention until it is ready to ship.

crlaurence.com

4

CRL TRANSACTION WINDOWS

Custom Made for Unlimited Variety



Multi-Lite with Drop Down and Transom



Inset Frame Window over TD1724 Transaction Drawer



Inset Frame Window with N555 Polished Steel Speak-Thru over Steel Shelf and Tray



Inset Frame Window with Plastic Glazing and Clear View Speak-Thru



Three Sided Frame over Tray inset in Counter



Clamp-On Frame Window with N666 Steel Speak-Thru over Steel Shelf and Tray





11 18 00/CRL BuvLine 6331



Inset Frame Window with N666 Steel Speak-Thru, 12" Steel Shelf and Tray



Inset Frame Window with Surround Sound over 18" Steel Shelf



Inset Frame Multi-Lite Window with N666 Steel Speak-Thru over Steel Shelf and Deal Trays




Clamp-On Frame Window with Special Hinged Panel Through Plastic Glazing

CRL BULLET RESISTANT SLIDING WINDOWS

Interior Window

- Interior Bullet **Resistant Slider**
- 0X, X0, 0X0, X0X Formats
- · Can Be Built into Larger Barriers
- Available in Level 1 or Level 3



- Exterior Bullet Resistant Slider
- Fully Weatherized
- 0X or X0 Formats
- · Available in Level 1 Only










Interior Multi-Lite Window with Surround Sound



CRL PRE-ENGINEERED MINI-BARRIERS

• An Elegant Alternative for Reception Security

CRL's pre-engineered Mini Barriers provide an elegant alternative for reception security. Available in bullet resistant levels 1 or 3, Mini Barriers can be used in conjunction with deal trays or transaction drawers. The pictured unit is designed for wall openings 54" wide x 48" high. Custom sizes and configurations are made to your specifications. Low profile aluminum extrusions and stainless steel clamps hold plastic glazing securely in place, maximizing vision area and air flow without the need for speak-thru devices or bulky hardware. Don't sacrifice aesthetics for security. Contact CRL's Transaction Hardware Department at Extension 7760 for more information on the Mini Barrier alternative.






CRL TRANSPARENT BULLET RESISTANT BARRIER SYSTEMS

- Banks
 Casino Cages
 Check Cashing
 Convenience Stores
- Government Offices Motels Pharmacies Police Stations





Seattle Justice Center, WA

Installation by J S Perrott & Co., Kirkland, WA

CRL engineers and fabricates complete Barrier Systems to your specifications. See our TH09 Catalog for the special clamps, channels, and sash employed. Available in Acrylic (UL 752 Level 1), Lexgard (UL 752 Level 3), and other plastic glazing materials. Call CRL for design assistance at (800) 421-6144 in the U.S., or (877) 421-6144 from Canada, and ask for Ext. 7760

2-5/8" 6-5/8

CRL BULLET RESISTANT DOORS




Materials: Frame - 14 Gauge Steel Door - 16 Gauge Steel

Glazing: 1-5/16" BR Glass Level 1; 1-7/8" BR Glass Level 3. Finish: Prime Painted


6

- Stock and Custom Sizes Available
 With or Without Vision Lite
 PROTECTION LEVEL
- UL 752 Level Level 1 or Level 3 Protection Available
- Interior or Exterior

Bullet Resistant Doors are fabricated from prime quality cold rolled steel, and include a baked-on rust inhibitive oxide primer. Standard components include: continuous geared aluminum hinge; surface mounted door closer; keyed cylinder lock; standard lever handles. Custom sizes and options are available on special order.



CRL BULLET RESISTANT FIBERGLASS PANELS



- Protective Panels for Lining Doors and Walls Surrounding Security Enclosures
- Available to Protection Level 3 (.44 Magnum S.P.S.A.)
- Typical Applications: Bank Teller Counters, Ticket Booths, Judge's Benches, Security Enclosures, and More


SPECIFICATIONS:

Material: Fiberglass - Reinforced Structural Polyester Laminate with Fiberglass Scrim. Finish: Panels may be covered with drywall, or clad with plastic laminate if desired. Cutting: Can be accomplished with a Circular Saw, Table Saw, Panel Saw or Saber Saw. We recommend the use of a carbide "Grit Edge" blade for ease of cutting. Drilling: High Speed Steel Drill Bits at a low speed.

CAT. NO.	PROTECTION Level*	PANEL THICKNESS	PANEL Size	PANEL WEIGHT	IMPACT Velocities*
BRF100	1 M.P.S.A.	1/4"	96" x 48"	84 Lbs.	1250 Ft./Sec.
BRF200	2 H.P.S.A.	3/8"	96" x 48"	110 Lbs.	1395 Ft./Sec.
BRF300	3 S.P.S.A.	7/16"	96" x 48"	138 Lbs.	1470 Ft./Sec.

* Levels per UL 752 Ballistic Performance Requirements. Test Specifications.

crlaurence.com



Package Receiver with Stainless Steel Doors CAT. NO. SIZE (W x D x H) PROTECTION SPR1 18-1/2" x 16" x 18-1/2" Level 1 18-1/2" x 16" x 18-1/2' SPR3 Level 3

4					
Packag	ge Receiver with V	ision Panel			
CAT. NO.	SIZE (W x D x H)	PROTECTION			
SPRVP1	18-1/2" x 16" x 18-1/2	2" Level 1			

SPRVP3 18-1/2" x 16" x 18-1/2"

Clear Package Receiver

CAT. NO SIZE (W x D x H) PROTECTION CPR1 16" x 16" x 16' Level 1 CPR31 Level 3 16" x 16" x 16' Level 3

Rotary Server with Vision Panel CAT. NO. SIZE (W x D x H) PROTECTION RSVW1 16" x 12-1/2" x 16" Level 1

7

e-mail: transaction@crlaurence.com | (800) 421-6144 ext. 7760 | Fax (800) 458-7496

additional transaction hardware products Pass-Thru Windows



<text>

VISIT THE WORLD of crlaurence.com

- Access to All CRL Products Through Our Easy-to-Use A to Z Product Index
- View All Current CRL Catalogs Online Direct E-Mail Connections to CRL Departments
- New CRL Products and Services Technical Articles and Product Support
- Ordering and Shipping Information Help in Using the Site
- CRL Locations with Addresses, Directions, Phone and Fax Numbers
- Account Policies and Credit Terms
 A Calendar of Industry Trade Shows



CRL Manufacturing

This 270,000 square foot facility is located in Vernon, California. CRL employees are at work using progressive QS-9000 manufacturing processes to make products to support the Glazing, Railing, Architectural, Construction, Industrial, and Automotive industries.



FOR MORE INFORMATION ON OTHER CRL

PRODUCTS SEE SWEET'S SECTIONS:

Technical Sales

C.R. Laurence Company has a Technical Sales Department to assist with design plans and installation questions. Your job can be made easier with the help of our Technical Sales Representatives who are trained in the newest Hardware Systems, and can offer you detailed diagrams and layout sheets. Ask for Extension 7760.

SWEETS 09-BULLET RESISTANT

and the second se

crlaurence.com | e-mail: transaction@crlaurence.com | (800) 421-6144 ext. 7760

8