

Paint and adhesive manufacturers have provided their recommendations for finishing materials suitable for use on EXTIRA. CMI provides this information, free of charge, to prospective users who must independently determine the suitability of such materials for its purpose. It is the user's responsibility to test and qualify all materials the user intends to use on EXTIRA. CMI does not guarantee the performance or compatibility of the materials listed in this document, or any other materials, nor does CMI bear any liability associated with the secondary treatment of EXTIRA. Samples of EXTIRA are available upon request for your testing purposes.

This document is not a guideline or direction meant to guarantee any result; it is strictly informational in nature. CMI makes no warranties or representations, express or implied, as to the accuracy, completeness, or any other aspect of the information in this document and CMI assumes no liability in connection with any use of the information. CMI provides this document to you on the condition that you will make your own complete assessment of the information given, prior to using these materials with EXTIRA. CMI has no knowledge of or control over your use of the information, and it is provided "as is" and without any warranty of any kind. Accordingly, CMI excludes all implied warranties, including but not limited to any warranty of merchantability or fitness for a particular purpose and warranties to the effect that the use of this information will not infringe any patent, copyright or trademark of any third party.

CMI welcomes information from you about your experience with the use of these materials or any other in the secondary treatment of EXTIRA.

### FINISHING:

Extira must be primed and painted or finished before use. Use a high quality exterior oil/alkyd solvent-based or acrylic latex primer system specifically designed for use on wood composite substrates. The final topcoat should be compatible with the primer system used. Ninety-degree (90°) edges should be eased where possible to improve paint coverage and to extend service life. Final qualification is the responsibility of the end user.

The companies listed below have tested paint systems for use with Extira. The following topcoats are not recommended by CMI or most paint manufacturers because of short service life, poor protection against UV light and a higher potential for performance problems:

- Shake and shingle paints, clear coatings, flat oil/alkyd paints topcoats, and vinyl acetate (PVA) base paints.
- Transparent and semi-transparent stains.

### FINISHING CONTACT INFORMATION:

#### One Shot, LLC.

Technical Support  
5300 Fifth Avenue  
P.O. Box 6369  
Gary, IN 46406  
Phone: 219.949.1684  
Email: asklouie@hotmail.com

#### Akzo Nobel Coatings, Inc.

Contact: Forest Flemming  
1431 Progress Ave.  
High Point, NC 27261  
Phone: 336.801.0820  
Email: forest.g.flemming@akzo-noble.com

#### Matthews Paint

Customer Service Group  
LakeView Corporate Park  
8201 – 100th Street  
Pleasant Prairie, WI 53158  
Phone: 800.323.6593  
Email: mpcmail@ppg.com

#### Sherwin Williams

Contact: Hal Shackelford  
Chemical Coatings  
P.O. Box 304  
Krum, TX 76249  
Phone: 940.482.7068  
Email: hal.h.shackelford@sherwin.com

#### T.J. Ronan Paint Corp

Contact: Bob Chlupsa  
749 East 135th Street  
Bronx, NY 10454  
Phone: 800.247.6626  
Email: ronanpaint@aol.com

#### Valspar

Contact: Brian Lewallen  
Global Wood Coatings Group  
1717 English Road  
High Point, NC 27261  
Phone: 800.395.7047  
Email: blewallen@valspar.com

**ADHESIVES:**

The following companies have tested Extira with the products listed below for the specific applications shown. Contact the manufacturer for final overlay compatibility, recommendation on specific usage, adhesive quantities and press conditions before using the product specified.

**EXTERIOR APPLICATIONS**

Glue Manufacturer	Glue System	Application
Ashland Performance Materials	Isoset WD3-A322/CX-47 (water based)	HPL
	Isogrip 2065D (moisture cure-urethane)	HPL
Forbo Adhesive	Everlock 2U131 (hotmelt polyurethane reactive adhesive)	HPL
	Everlock 2U145 (hotmelt polyurethane reactive adhesive)	HPL
	Everlock 2U259 (hotmelt polyurethane reactive adhesive)	HPL
Franklin International	Titebond Heavy Duty Construction Adhesive (solvent based)	Extira to Extira
	Titebond Heavy Duty Construction Adhesive (solvent based)	Extira to Extira
	Titebond Trowelable Construction Adhesive (solvent based)	Extira to Extira
	Titebond Polyurethane Subfloor Adhesive	Extira to Extira
	Franklin 811 Plus Urethane Wood Floor Adhesive	Extira to Extira
H.B. Fuller Company	Titebond II	Extira to Extira, wood veneer
	RK3379001 (Precatalyzed PVAc)	HPL, Extira to Extira, and wood veneer
	UR0218MF (liquid moisture-cure urethane)	HPL, Extira to Extira,
National Casein	NP2075T (hotmelt polyurethane reactive)	HPL, Extira to Extira, and wood veneer
	MB 330 (melamine powder)	wood veneer
	MUF 4301 (melamine powder)	wood veneer
	WP2457/K-4 (emulsion polymer w/catalyst)	wood veneer

**INTERIOR APPLICATIONS**

Wilsonart Adhesives	WA 950/951 (Solvent contact adhesive)	Extira to HPL
	WA H2O (water basted contact adhesive)	Extira to HPL
	WA 3000 (PVA for postforming)*	Extira to HPL
	WA 3132 (Hot press PVA)*	Extira to HPL
	WA 3301 (PVA)*	Extira to HPL
Sovereign Specialty Chemicals	PG107R (contact adhesive)	Extira to HPL
	PG565R (contact adhesive)	Extira to HPL

\*contact Wilsonart for specific application instruction

**ADHESIVE CONTACT INFORMATION:**

**Ashland Performance Materials**

Contact: Gary Schaeffer  
802 Harmon Avenue  
Columbus, OH 43223  
Phone: 614.232.8564  
Email: gschaeffer@ashland.com

**Forbo Adhesives**

Contact: Rick Delaney  
523 Davis Drive, Suite 400  
Durham, NC 27713  
Phone: 610.869.9940  
Email: rick.delaney@forbo.com

**Franklin International**

Contact: Dale E. Zimmermann  
2020 Bruck Street  
Columbus, OH 43207  
Phone: 800.347.4583  
Email: contechserv@franklininternational.com

**H.B. Fuller Company**

Contact: Tom Howard  
1200 Willow Lake Blvd.  
Vadnais Heights, MN 55110  
Phone: 651.236.5695  
Email: tom.howard@hbfuller.com

**National Casein of New Jersey**

Contact: Ken Blake  
401 Martha's Lane  
Riverton, NJ 08077  
Phone: 856.829.1880  
Email: blake@nationalcasein.com

**Wilsonart Adhesives**

Contact: Dave Berry  
10601 NW Dodgen Loop  
Temple, TX 76503  
Phone: 254.207.6701  
Email: berryd@wilsonart.com

**Sovereign Specialty Chemicals**

Contact: Vince Pearson  
6315 Wiehe Road  
Cincinnati, OH 45237  
Phone: 513.351.1300  
web: www.sovereignsc.com