



VISTA® V3

Series electric strike



Product Overview

- Affordable pricing with enormous versatility
- Grade 2 electric strike for medium grade applications
- Genuine value and reliability from the market leader

Specifications

- ANSI/BHMA A156.31 Grade 2

Standard Features

- Small strike body fits in many competitive cutouts with no modification to the frame
- 8 flexible faceplate options
- Modular components allow you to adjust depth as needed
- Up to 1/4" horizontal adjustability
- Accommodates 1/2 - 5/8" cylindrical latchbolt (5/8" with 1/8" door gap)
- Static strength 1,000 lbs.
- Dynamic strength 50 ft-lbs.
- Endurance 500,000 cycles
- Non-handed
- Available in fail secure (fail safe version available Fall 2009)
- One year limited warranty

Frame Applications

- Metal
- Wood

Electrical

- .20 Amps @ 12VDC/VAC
- .10 Amps @ 24VDC/VAC
- DC continuous duty/AC intermittent duty only

Faceplates

- Option 1 4-7/8" x 1-1/4" square corner
- Option 1A 4-7/8" x 1-1/4" radius corner
- Option 2 7-15/16" x 1-7/16" radius corner
- Option 3 6-7/8" x 1-1/4" radius corner
- Option 4 9" x 1-3/8" radius corner & flat faceplate
- Option 5 3-1/2" x 1-3/8" square corner & flat faceplate
- Option 6 7-15/16" x 1-7/16" radius corner
- Option 7 2-3/4" x 1-1/18" square corner

Available Finishes*

- 630, 613, 606
- 630, 613, 606
- 630, 613, 606
- 630, 613, 606
- 630
- 606C, 626
- 626
- 626

* Finish Key

- 630 - Satin stainless steel finish
- 613 - Bronze toned finish
- 606 - Satin bronze finish
- 626 - Satin chrome finish
- 606C - Gold finish