






Traco Blast™ Product Selection Guide



BLAST RESISTANT WINDOWS

PRODUCT	DESCRIPTION	BLAST MODEL	FRAME DEPTH	CONFIGURATION	WATER PRESSURE (PSF)	TEST SIZE	BLAST (PSI)	GSA BLAST RATING	DOD BLAST RATING (HAZARD)	LARGE MISSILE IMPACT OPTION
PROJECTED 	PROJECT OUT	06B2500	2-1/4"	X	12	36-1/2" X 16-1/2"	6.2	1	NONE	
	PROJECT OUT / FIXED	06B3510	3-1/4"	X/0	12	51" X 70-1/2"	5.8	1	NONE	✓
	PROJECT OUT / FIXED	12B3510	3-1/4"	X/0	12	51" X 70-1/2"	12.1	2	MINIMAL	✓
	FIXED / PROJECT OUT	NXB3500	3-1/4"	0/X	15	60" X 72"	5.8	2	MINIMAL	✓
	FIXED / PROJECT OUT	NXB3500	3-1/4"	0/X	15	48" X 66"	6.2	2	MINIMAL	✓
	FIXED / PROJECT OUT	NXB3500	3-1/4"	0/X	15	24" X 40"	6.0	2	MINIMAL	✓
CASEMENT 	FIXED - OUTSWING	06B3102	3-1/4"	0-X	12	51" X 70-1/2"	5.9	1	NONE	
	OUTSWING - FIXED	06B3102	3-1/4"	X-0	12	51" X 70-1/2"	5.9	1	NONE	
	FIXED-OUTSWING	NXB3100	3-1/4"	0-X	15	60" X 72"	6.5	2	MINIMAL	✓
	OUTSWING - FIXED	NXB3100	3-1/4"	X-0	15	60" X 72"	6.5	2	MINIMAL	✓
	FIXED - OUTSWING	NXB3100	3-1/4"	0-X	15	48" X 66"	6.1	2	MINIMAL	✓
	OUTSWING - FIXED	NXB3100	3-1/4"	X-0	15	48" X 66"	6.1	2	MINIMAL	✓
	LH OUTSWING	NXB3100	3-1/4"	X	15	24" X 40"	6.4	2	MINIMAL	✓
	RH OUTSWING	NXB3100	3-1/4"	X	15	24" X 40"	6.4	2	MINIMAL	✓
FIXED 	FIXED	06B3800	3-1/4"	0	15	47-1/4" X 67-1/2"	6.0	1	NONE	✓
	FIXED	06B3800	3-1/4"	0	15	49-3/4" X 69-1/4"	6.0	2	MINIMAL	✓
	FIXED	06B3800	3-1/4"	0	15	48" X 66"	6.4	2	MINIMAL	✓
	FIXED	06B3800	3-1/4"	0	15	51" X 70-1/2"	5.8	2	MINIMAL	✓
	FIXED	06B3800	3-1/4"	0	15	51" X 70-1/2"	6.3	3B	LOW	✓
	FIXED	06B3800	3-1/4"	0	15	51" X 70-1/2"	6.0	1	NONE	✓
	FIXED	10B3800	3-1/4"	0	15	49-3/4" X 69-1/4"	9.9	3B	LOW	✓
	FIXED	12B3800	3-1/4"	0	15	51" X 70-1/2"	11.8	2	MINIMAL	✓
	FIXED	NXB3800	3-1/4"	0	15	60" X 72"	6.1	2	MINIMAL	✓
	FIXED	NXB3800	3-1/4"	0	15	48" X 66"	5.9	2	MINIMAL	✓
	FIXED	NXB3800	3-1/4"	0	15	24" X 40"	6.3	2	MINIMAL	✓
	SLIDING 	SINGLE SLIDE	06B6800	3-1/4"	X0	10	67-3/4" X 49-1/2"	6.2	3A	VERY LOW
SINGLE SLIDE		06B6800	3-1/4"	0X	10	67-3/4" X 49-1/2"	6.2	3A	VERY LOW	✓
PROJECT OUT/SINGLE SLIDE		06B2500/06B6800	3-1/4"	X/X0	10	56-1/2" X 68-3/8"	6.1	2	MINIMAL	
PROJECT OUT/SINGLE SLIDE		06B2500/06B6800	3-1/4"	X/0X	10	56-1/2" X 68-3/8"	6.1	2	MINIMAL	
HUNG 	SINGLE HUNG	06B9100	3-1/4"	0/X	12	51" X 70-1/2"	5.9	1	NONE	✓
	TWIN SINGLE HUNG	06B9100	3-1/4"	0/X-0/X	12	60" X 60"	6.4	2	MINIMAL	
	TWIN SINGLE HUNG	06B9100	3-1/4"	0/X-0/X	12	72" X 72"	6.3	2	MINIMAL	

Window products tested according to Unified Facilities Criteria (UFC) 4-010-01 "DOD Minimum Antiterrorism Standards for Buildings", ASTM 1642 "Standard Test Method for Glazing and Glazing Systems Subject to Airblast Loadings", and GSA "Standard Test Method for Window and Glazing Systems Subject to Dynamic Over Pressure Loadings". Options other than those listed above are available based on your specific project requirements. Gray color bar indicates Traco NX Products featuring NexGen™ Technology.